

# **Evacuation Chair Operation Handbook**





# Use of your versa and versa-elite evacuation chairs

The **exitmaster versa** and **versa-elite** products have been carefully designed and manufactured to provide an easy, safe and dependable method of evacuating persons who are (or may become) unable to use normal exit routes to safety in event of a fire or emergency. The products provide downstairs and level evacuation with only one operator and upstairs/carrying evacuation with two or more operators.

## FOR AUTHORISED USE BY TRAINED OPERATORS These instructions must be read and followed in detail

#### **Evacuation Plan**

The use of the evacuation chairs must be part of an Evacuation Plan that meets current legislative requirements.

#### Passengers

Where possible, persons that the evacuation chairs are provided for should be familiar and comfortable with the use of the product.

#### **Operators**

Operators must have adequate physical and communication ability to carry out the tasks involved safely and competently. Appropriate clothing, including stout closed toe and flat soled footwear should be worn.

#### Stairway/Route

Stairways and exit routes should be in good condition, clear of obstructions and litter and previously checked for compatibility with the evacuation chairs.

#### Manual Handling

Correct manual handling techniques must be used.

#### **Product Training**

Operator training and refresher training are available through the supplier and will be tailored to suit customer's requirements. Training includes the operator riding as a passenger. A regular practice routine must be maintained and records of trained/authorised operators retained. In all cases the suitability of an operator is at the instructor's discretion.

#### **Cascade/Peer Trainers**

Suitably experienced operators with relevant knowledge of building/premises management and Health & Safety issues may be nominated by the customer and trained as cascade/peer trainers.

### Liability

The manufacturer accepts no liability for any use outside of the intended and published correct use(s) and specification of this product.



# B



- 6. Slide spring latches to centre
- 5. Secure latch bar with safety lock

 Fully raise handle and release spring latches Ensure spring latches engage outwards as shown below

Safety Note: Never adjust handle with passenger seated



Tip: Communicate with passenger at every stage for reassurance



**Safety Note:** Apply brakes if leaving chair and passenger unattended on level surfaces **Tip:** You may also turn with the chair inclined at the balance point

 Slide spring latches to centre and down into slot

2. Push buttons to remove handles upwards

**Safety Note:** Never adjust/remove handle with passenger seated

5. Assist passenger into chair



**Tip:** Use leg straps and armrests as required - if fitted

- Turn handle 180° and replace to lower position (curving towards operator)
- 4. Release spring latches

Ensure spring latches engage outwards as shown below



7. Tilt chair backwards at bottom step to raise front handles

 Using 2 or more operators as necessary lift the chair and climb the stairs

**Note:** Avoid contact between chair and stairs as you climb

www.easycaresystems.co.uk

## **Before storing**

- 1. Apply brakes
- 2. Lower handle (curving away from operator)
- 3. Release safety lock
- 4. To fold raise latch bar and lift front of seat
- **5.** Pass seat belt around tracks and secure closed
- 6. Release brakes for easy transportation when folded



#### Storage

The exitmaster versa and versa-elite evacuation chairs should be stored off the floor, with the brakes applied and in a clean, dry environment.

A wall bracket is supplied which holds the handle of the chair centrally with the tracks towards the wall.

Ensure that the wall bracket is securely fixed in a suitable location and use the fitted cover for further protection.

A security alarm and robust storage cabinet are also available - see Optional Extras.

#### Care/Maintenance/Parts

The evacuation chairs must be kept clean and accessible at all times. Any damage or misfunction should be reported and remedied immediately.

Annual safety checks and ongoing maintenance programmes are available from your supplier.

Use of aggressive cleaning products, solvents, oils etc. may damage the finish and function.

Replacement parts are readily available and fitting can be arranged by an authorised technician through your supplier. Only manufacturer's genuine replacement parts should be used.

#### Guarantee

A comprehensive 12 month guarantee applies within the scope of the products published use and specification. Misuse, neglect, damage, use of non genuine parts and unauthorised repair will void the guarantee cover.

#### Contact Us

Units 5 and 6 Lower Vicarage Road Southampton Hampshire SO19 7RJ T: 02380 420678 E: info@easycaresystems.co.uk www.easycaresystems.co.uk

